No. DoP-120874

- 1. Product Type:
 Designer Radiators

 2. Unique Identification Code(s):
 120874- Calverley Anthracite 795x500mm 02.CVTR57A
- **3.** Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by manufacturer:

In heating systems in buildings

- 4. Manufacturer: Manufactured by Towelrads.com Ltd Units 4 & 5 Maidenhead Trade Park Priors Way Maidenhead Berkshire SL6 2GQ
- 5. Authorised Representative: N/A

7.

6. System of System or systems of assessment and verification of constancy of performance of the construction product set out in Annex V of the CPR:

	System 3	
Harmonised Standard:	BS EN442-1&2: 2014	
Notified Body:	POLITECNICO DI MILANO – VIA RAFFAELE LAMBRUSCHINI,	

8. Notified Body: POLITECNICO DI MILANO – VIA RAFFAELE LAMBRUSCHINI, 4 (ZONA BOVISA) 20156 MILANO ITALY

Performed the assessment and evaluation of the product under system 3:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class A1	Specification
Release of dangerous substances	NPD	
Pressure tightness	Pass (1300 kPa)	
Resistance to Pressure	Pass (1690kPa)	
Surface temperature	Maximum 90 deg C	
Rated thermal output	Φ = (2.16356 K _M x 1.24595n) x ΔT ⁿ	EN 442-1&2 -2014
Thermal output in different operating conditions (characteristic curve)	343 Watts	
	10 year	
Durability	manufacturer's	
	warranty	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and function: Richard Bland – Operations Manager

Place and date of issue:

Queensgate House, Bracknell, Berkshire RG12 1RB 04/12/19

2800

No. DoP-120875

- 1. Product Type:
 Designer Radiators

 2. Unique Identification Code(s):
 120875- Calverley Anthracite 1245x500mm 02.CVTR512A
- **3.** Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by manufacturer:

In heating systems in buildings

- 4. Manufacturer: Manufactured by Towelrads.com Ltd Units 4 & 5 Maidenhead Trade Park Priors Way Maidenhead Berkshire SL6 2GQ
- 5. Authorised Representative: N/A

4 (ZONA BOVISA) 20156 MILANO ITALY

7.

8.

6. System of System or systems of assessment and verification of constancy of performance of the construction product set out in Annex V of the CPR:

Notified Body:	POLITECNICO DI MILANO – VIA RAFFAELE LAMBRUSCHINI,
Harmonised Standard:	BS EN442-1&2: 2014
	System 3

Performed the assessment and evaluation of the product under system 3:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class A1	Specification
	NPD	-
Release of dangerous substances		-
Pressure tightness	Pass (1300 kPa)	
Resistance to Pressure	Pass (1690kPa)	
Surface temperature	Maximum 90 deg C	
	Φ = (2.16356 K _M x	EN 442-1&2 -2014
Rated thermal output	1.24595n) x ΔT ⁿ	
Thermal output in different operating conditions	503 Watts	
(characteristic curve)		
	10 year	
Durability	manufacturer's	
	warranty	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

04/12/19

Signed for and on behalf of the manufacturer by:

Name and function: Richard Bland – Operations Manager

Place and date of issue: Queensgate House, Bracknell, Berkshire RG12 1RB

Read

No. DoP- 127003

- 1. Product Type:
 Designer Radiators

 2. Unique Identification Code(s):
 127003– Calverley Chrome 795x500mm 02.CVTR57C
- **3.** Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by manufacturer:

In heating systems in buildings

- 4. Manufacturer: Manufactured by Towelrads.com Ltd Units 4 & 5 Maidenhead Trade Park Priors Way Maidenhead Berkshire SL6 2GQ
- 5. Authorised Representative: N/A
- 6. System of System or systems of assessment and verification of constancy of performance of the construction product set out in Annex V of the CPR:
- System 3

 7. Harmonised Standard:
 BS EN442-1&2: 2014

 8. Notified Body:
 POLITECNICO DI MILANO VIA RAFFAELE LAMBRUSCHINI,
- 4 (ZONA BOVISA) 20156 MILANO ITALY

Performed the assessment and evaluation of the product under system 3:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class A1	
Release of dangerous substances	NPD	
Pressure tightness	Pass (650 kPa)	
Resistance to Pressure	Pass (840kPa)	
Surface temperature	Maximum 90 deg C	
Rated thermal output	$Φ = (1.46297 K_M x)$ 1.18760n) x ΔT ⁿ	EN 442-1&2 -2014
Thermal output in different operating conditions (characteristic curve)	227Watts	
	10 year	
Durability	manufacturer's	
	warranty	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and function:

Paul Hamilton – Director

Place and date of issue:

Queensgate House, Bracknell, Berkshire RG12 1RB 01/12/2016

PMAam en

No. DoP- 127004

- 1. Product Type:
 Designer Radiators

 2. Unique Identification Code(s):
 127004– Calverley Chrome 1245x500mm 02.CVTR512C
- **3.** Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by manufacturer:

In heating systems in buildings

- 4. Manufacturer: Manufactured by Towelrads.com Ltd Units 4 & 5 Maidenhead Trade Park Priors Way Maidenhead Berkshire SL6 2GQ
- 5. Authorised Representative: N/A
- 6. System of System or systems of assessment and verification of constancy of performance of the construction product set out in Annex V of the CPR:
- System 3

 7. Harmonised Standard:
 BS EN442-1&2: 2014

 8. Notified Packy
 POLITECNICO DI MULANO, MA PAFEAELE LAMPRUSCHU
- 8. Notified Body: POLITECNICO DI MILANO VIA RAFFAELE LAMBRUSCHINI, 4 (ZONA BOVISA) 20156 MILANO ITALY

Performed the assessment and evaluation of the product under system 3:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class A1	
Release of dangerous substances	NPD	
Pressure tightness	Pass (650 kPa)	
Resistance to Pressure	Pass (840kPa)	
Surface temperature	Maximum 90 deg C	
Rated thermal output	$Φ = (1.46297 K_M x)$ 1.18760n) x ΔT ⁿ	EN 442-1&2 -2014
Thermal output in different operating conditions (characteristic curve)	333Watts	
	10 year	
Durability	manufacturer's	
	warranty	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and function:

Paul Hamilton – Director

Place and date of issue:

Queensgate House, Bracknell, Berkshire RG12 1RB 01/12/2016

PMAam en