

01.TRVC** Chelsea Corner Thermostatic Radiator Valves

Chrome

01.TRVCCH

Antique Brass

01.TRVCAB

Satin Nickel

01.TRVCSN

Thermostatic valves are typically used for regulating the fluid flow to the radiators of central heating systems. They are provided with a regulating element which automatically controls the opening of the valve to keep the ambient temperature of the room where they are installed constant at the set value.

Turn the wheel handle until the mark corresponding to the required room temperature appears above the top of the shroud. The bottom mark (30°C) will appear when the wheel handle is turned fully anti-clockwise (valve is fully open).

When the wheel handle is turned fully clockwise it will feel closed. In this position, it operates when the temperature falls below 5°C to provide frost protection.



Shown in Satin Nickel

TECHNICAL SPECIFICATION:

- With thermostatic head and lockshield.
- Built-in sensor with liquid-filled element
- Fully tested to 10 bar
- Max pressure difference: 0.8 bar
- 2 Year Guarantee
- Nominal flow rate 173kgs/h
- Max flow temperature 120°C
- Can be mounted horizontally or vertically
- Weight 0.60kg

THE TUNBRIDGE WELLS
Brassware Co.

Chrome

01.TRVCCH

Antique Brass

01.TRVCAB

Satin Nickel

01.TRVCSN

