

Technical Data Sheet

ASTER



Box Contents:

Aster Mirror – Circular, Pill or Oval: Instructions booklet | 2x wall plugs | 2x screws Aster Mirror – Square or Rectangular: Instructions booklet | 4x wall plugs | 4x screws | 2x wall brackets

Materials

Frame Material: Extruded Aluminium

Glass: 5mm PVC Backed

FAQ's:	Units	AS60ALR	AS49ALE	AS40ALC	AS70ALC	AS80ALC	AS100ALC	AS120ALC	AS80ALR	AS50ALP
Can the mirror be hung landscape?	-	No			Yes			No		Yes
What is the thickness of the mirror glass?	mm	5								
Is the mirror IP44 rated?	-	Yes – Suitable for use in bathroom zone 2								
What size fuse should I use?	-	Seek the advice of an electrician								
What is the total power consumption?	W	32	31	34.5	56.9	60.9	71.8	83.8	59	37.3
Does the mirror have an energy rating?	-	Yes – It has an energy rating of: F								
What is the colour of the light and the Kelvin rating?	К	2700 - 6000								
What is the Lumen of the LEDs?*	Lms	1734	1632	1989	2091	2652	2856	3264	2652	2040
What is the wattage of the lights?	W	17	16	19.5	22	26	28	32	24	20
Where is the IR sensor/rocker switch located?	-	Front middle			Front bottom right			Front middle		
Can the LED lighting be replaced?	-	No**								
Can the IR sensor be replaced?	-	Yes								
What is the output of the demister pad?	W	15			34.9		43.8	51.8	34.9	17.3
What are the dimensions of the demister pad? (L x W)	mm	200 x 300			310 x 450		250 x 700	230 x 900	310 x 450	230 x 300
How do I turn on the demister pad?	-	The demister pad will turn on when the LEDs are turned on.								
Are illuminated mirrors supplied with mains cable?	-	All illuminated mirrors are supplied with a removeable 500mm mains cable.								

Dimensions are subject to change; customers are advised to measure actual product before commencing installation.

Fixing point dimensions are for guidance only/the positions of wall fixing must be checked when product is received.

 $^{{\}bf *The\ Lumen\ represents\ the\ output\ of\ the\ LED.\ This\ may\ vary\ depending\ on\ the\ diffuser\ material\ i.e.,\ glass\ or\ acrylic.}$

^{**}The LEDs are not replaceable to maintain the integrity of the product's resistance to moisture ingress.

TAVISTOCK

